

Mytrunnion-4G

5-Axis Machining Center

[View product video](#)



Specifications

Table Size:	15.7" (400mm) round dia.
Travel (X, Y, Z):	24" x 24" x 19.7" (610 x 610 x 500mm)
Travel (A, C):	-120~+30 deg. /0~360 deg.
Spindle Taper:	NST No. 40
Spindle Speed:	40~15,000rpm
Tool Storage Capacity:	60 Pcs. (Opt. 100T)
Tool Change Time (T-T/C-C):	2.2 Sec. /5.8 Sec.
Rapid Feed (X, Y, Z):	1969ipm (50m/min) X & Y, 985ipm (25m/min) Z
Rapid Feed (A, C):	18,000 deg. /min (50rpm)
Power Requirement:	45KVA

Features

- Ideal for ultra-high precision simultaneous 5-axis machining
- Positioning Accuracy: $\pm 0.000079"$ Full Stroke, Repeatability: $\pm 0.000039"$
- Sliding overhead door allows for easy workpiece loading/unloading
- Powerful #40, 15,000rpm, 15HP Direct Drive, Dual Contact Spindle Optional HSK-A63 Spindle Configuration available
- Highly Rigid, Ultra-High Precision Roller Gear Cam Table in the 4th & 5th Axes
- Expansive 21.7"Dia. x 15.7"H (550 x 400mm) work envelope beats the competition
- Highest grade meehanite cast iron construction for superior vibration absorption and improved surface finishes